

For Serial Number 9J1264 and Higher

Parts Page Reorder No. PD01•03R
Effective January, 2001
Supersedes PD96•33

.4 Hp/7°/Rear Exhaust Disc Sander

Air Motor and Machine Parts


Models:
52500 — 2" Disc Sander

KEY	
O	Oil: O ₁ = Air Lube
A	Adhesive: A ₈ = Loctite #567
T	Torque: N•m x 8.85 = In. - lbs.

WARNING

Always operate, inspect and maintain this tool in accordance with the Safety Code for portable air tools (ANSI B186.1) and any other applicable safety codes and regulations. Please refer to Dynabrade's Warning/Safety Operating Instructions for more complete safety information. See inside for Important Operating, Maintenance and Safety Instructions.

Index Key	
No.	Part # Description
1	51344 2" Dynapad
2	50133 Adapter
3	01560 Exhaust Cover
4	01580 Silencer
5	02649 Bearing
6	54529 Shim Pack (3/pkg.)
7	01478 Front Bearing Plate
8	01479 Spacer
9	50767 Pin (2)
10	01480 Blades (4/pkg.)
11	01594 Rotor
12	01476 Cylinder
13	02673 Rear Bearing Plate
14	02696 Bearing
15	02679 Shield
16	01546 Housing
17	01548 Gasket
18	01461 Lock Nut
19	01558 Collar
20	95523 O-Ring
21	01470 Insert
22	01587 Housing - 52500
23	01448 Throttle Lever
24	01462 Safety Throttle Lever
25	12132 Pin
26	95558 Retaining Ring
27	01449 Valve Stem
28	95730 O-Ring
29	01024 O-Ring
30	01469 Speed Regulator
31	94520 Muffler Assembly
32	01464 Seal
33	01472 Tip Valve
34	01468 Spring
35	01642 Air Control Ring
36	95711 Retaining Ring
37	95438 O-Ring
38	94521 Muffler Base
39	94524 Sintered Muffler
40	94525 Felt Muffler
41	94522 Muffler Cap
42	95375 O-Ring
43	94526 Spacer
43	94523 Inlet Adapter



Important Operating, Maintenance and Safety Instructions

Carefully read all instructions before operating or servicing any Dynabrade® Abrasive Power Tool.

Warning: Hand, wrist and arm injury may result from repetitive work motion and overexposure to vibration.

Important: All Dynabrade rotary vane air tools must be used with a Filter-Regulator-Lubricator to maintain all warranties.

Operating Instructions:

Warning: Eye, face, respiratory, sound and body protection must be worn while operating power tools. Failure to do so may result in serious injury or death. Follow safety procedures posted in workplace.

1. With power source disconnected from tool, securely fasten abrasive/accessory on tool.
2. Install air fitting into inlet bushing of tool. **Important:** Secure inlet bushing of tool with a wrench before attempting to install the air fitting to avoid damaging valve body housing.
3. Connect power source to tool. Be careful not to depress throttle lever in the process.
4. Air tools are not intended for use in explosive atmospheres and are not insulated for contact with electrical power sources. Sanding/Grinding certain materials can create explosive dust. It is the employers responsibility to notify the user of acceptable dust levels. Sanding/Grinding can cause sparks which can cause fires or explosions. It is the users responsibility to make sure the work area is free of flammable materials.

Maintenance Instructions:

1. Check tool speed regularly with a tachometer. If tool is operating at a higher speed than the RPM marked on the tool or operating improperly, the tool should be serviced to correct the cause before use.
2. Some silencers on air tools may clog with use. Clean and replace as required.
3. All Dynabrade rotary vane air motors should be lubricated with two drops of Dynabrade Air Lube (P/N 95842: 1 pt. 473 ml.) every four hours of use.
4. It is strongly recommended that all Dynabrade rotary vane air tools be used with a Filter-Regulator-Lubricator to minimize the possibility of misuse due to unclean air, wet air or insufficient lubrication. Dynabrade recommends the following: 11405 Air Line Filter-Regulator-Lubricator — Provides accurate air pressure regulation, two-stage filtration of water contaminants and micro-mist lubrication of pneumatic components. Operates 40 SCFM @ 100 PSIG has 3/8" NPT female ports.
5. Use only genuine Dynabrade replacement parts. To reorder replacement parts, specify the number and serial number of your machine.
6. A Motor Tune-Up Kit (P/N 96049) is available which includes assorted parts to help maintain motor in peak operating condition.
7. Mineral spirits are recommended when cleaning the tool and parts. Do not clean tool or parts with any solvents or oils containing acids, esters keytones, chlorinated hydrocarbons, nitro carbons or chemicals that have a low flash point (example: WD-40®).

Safety Instructions:

Products offered by Dynabrade should not be converted or otherwise altered from original design without expressed written consent from Dynabrade, Inc.



- **Important:** User of tool is responsible for following accepted safety codes such as those published by the American National Standards Institute (ANSI).
- Operate machine for one minute before application to workpiece to determine if machine is working properly and safely before work begins.
- Always disconnect power supply before changing abrasive/accessory or making machine adjustments.
- Inspect abrasives/accessories for damage or defects prior to installation on tools.
- Please refer to Dynabrade's Warning/Safety Operating Instructions Tag (Reorder No. 95903) for more complete safety information.
- **Warning:** Hand, wrist and arm injury may result from repetitive work, motion and overexposure to vibration.

Notice

All Dynabrade motors use the highest quality parts and metals available and are machined to exacting tolerances. The failure of quality pneumatic motors can most often be traced to an unclean air supply or the lack of lubrication. Air pressure easily forces dirt or water contained in the air supply into motor bearings causing early failure. It often scores the cylinder walls and the rotor blades resulting in limited efficiency and power. Our warranty obligation is contingent upon proper use of our tools and cannot apply to equipment which has been subjected to misuse such as unclean air, wet air or a lack of lubrication during the use of this tool.

One Year Warranty

Following the reasonable assumption that any inherent defect which might prevail in a product will become apparent to the user within one year from the date of purchase, all equipment of our manufacture is warranted against defects in workmanship and materials under normal use and service. We shall repair or replace at our factory, any equipment or part thereof which shall, within one year after delivery to the original purchaser, indicate upon our examination to have been defective. Our obligation is contingent upon proper use of Dynabrade tools in accordance with factory recommendations, instructions and safety practices. It shall not apply to equipment which has been subject to misuse, negligence, accident or tampering in any way so as to affect its normal performance. Normally wearable parts such as bearings, contact wheels, rotor blades, etc., are not covered under this warranty.

Model Number	Motor HP (W)	Motor RPM	Sound Level	Air Flow Rate CFM/SCFM (LPM)	Air Pressure PSIG (Bars)	Spindle Thread	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
52500	.4 (298)	25,000	87 dB(A)	3/20 (566)	90 (6.2)	1/4"-20 male	1.3 (.6)	9 (229)	3-3/4 (95)

Additional Specifications: Air Inlet Thread 1/4" NPT • Hose I.D. Size 1/4" (8 mm)

(PD01-03R)

Disassembly/Assembly Instructions - .4 Hp./17°/Rear Exhaust

Important: Manufacturer's warranty is void if tool is disassembled before warranty expires

Notice: Dynabrade strongly recommends the use of their 52296 Repair Collar (sold separately) during assembly/disassembly activities. Failure to use this collar will highly increase the risk of damage to the valve body of this tool. Please refer to parts breakdown for part identification.

To Disassemble:

1. Disconnect tool from power source.
2. Secure air tool in vise using 52296 Repair Collar.
3. Remove 01594 Back-Up Pad.
4. With an adjustable pin wrench, remove 01560 Exhaust Cover by turning counter-clockwise.
5. Pull motor assembly from housing.
6. Reposition motor housing in vise so inlet bushing is facing upwards.
7. Remove 94523 Inlet Bushing and muffler assembly from valve body housing. Using needle nose pliers, remove spring, tip valve and seal.
8. Remove 95711 Retaining Ring from inlet adapter and disassemble muffler assembly.
9. Using a 2.5 mm diameter drift pin and a hammer, tap 12132 Pin out from housing and remove throttle lever.
10. Remove 95558 Retaining Ring and push 01469 Speed Regulator from housing.

Motor Disassembly:

1. Remove 50133 Adapter from rotor shaft by inserting 3 mm hex wrench through adapter and into rotor shaft. Twist adapter from shaft.
2. Remove 01478 Front Bearing Plate, cylinder, blades (4) and 01479 Spacer from rotor. **Note:** 02649 Bearing is a slip fit into 01478 Front Bearing Plate.
3. Press rotor from 02678 Rear Bearing Plate. Press 02696 Bearing from rear bearing plate. (96210 Bearing Removal Press Tool is available.)

Motor Disassembly Complete.

Motor Assembly:

Important: Be sure parts are clean and in good repair before assembling.

1. Place 01594 Rotor in padded vise with threaded spindle facing upwards.
2. Slip 01479 Spacer onto rotor.
3. Place a .002" shim into 01478 Front Bearing Plate as an initial spacing (**Note:** 54529 Shim Pack contains .001" and .002" shims) and slip 02649 Bearing into plate.
4. Install bearing/bearing plate assembly onto rotor.
5. Tighten 50133 Adapter onto Rotor (torque to 17 N•m/150 in. - lbs.).
6. Check clearance between rotor and bearing plate by using a .001" feeler gauge. Clearance should be at .001" to .0015". Adjust clearance by repeating steps 1-5 with different shim if necessary.
7. Once proper rotor/gap clearance is achieved, install well lubricated 01480 Blades (4) into rotor slots. Dynabrade air lube P/N 95842 is recommended for lubrication.
8. Install cylinder over rotor. Be sure air inlet holes of cylinder face away from front bearing plate and that the pin in the front bearing plate aligns correctly with the pin-hole in the cylinder.
9. Press against outer race of 02696 Rear Bearing and install into 02673 Rear Bearing Plate (96242 Bearing Press Tool available). Press bearing/bearing plate assembly onto rotor. Be sure that pin and air inlet holes line-up with pin slot and air inlet holes in cylinder.
Important: Fit must be snug between bearing plates and cylinder. A loose fit will not achieve the proper preload of motor bearings. If too tight, rotor will not turn freely. Rotor must then be lightly tapped at press fit end so it will turn freely while still maintaining a snug fit.
10. Secure motor housing in vise using 52296 Repair Collar with motor cavity facing upwards.
11. Install motor assembly into housing. Be sure motor drops all the way into housing.
12. Insert 01580 Silencer into 01560 Exhaust Cover and install onto motor housing. Apply #567 Loctite (or equivalent) to housing threads. (torque to 28 N•m/250 in. - lbs.).
13. Motor adjustment must now be checked. With motor housing still mounted in vise, pull end of rotor and twist (10-15 lbs. force), rotor should turn freely without drag. If drag or rub is felt, then increase preload or remove shim. Also, push end of rotor and twist (10-15 lbs. force), rotor should turn freely without drag. If drag or rub is felt, then deload or add shim.

Motor Assembly Complete.

Valve Body Assembly:

1. Insert 01469 Speed Regulator with valve stem and O-Rings installed, into housing, secure with 95558 Retaining Ring.
2. Place seal into housing. Using tweezers or needle nose pliers, place the tip valve into the housing so that the pin goes into the valve stem hole of regulator assembly.
3. Place 01468 Spring into housing with small end towards valve assembly.
4. Assemble muffler assembly. Slip 94523 Inlet Adapter through muffler assembly and secure with 95711 Retaining Ring.
5. Install air control ring into valve body housing.
6. Apply #567 Loctite PST Pipe Sealant (or equivalent) to threads of inlet bushing and install muffler assembly onto valve body (torque 23.0 N•m/200 in. lbs.).
7. Install throttle lever and 12132 Pin. Remove from vise.

Tool Assembly Complete. Please allow 30 minutes for adhesives to cure before operating tool.

Important: Motor should now be tested for proper operation at 90 PSIG. If motor does not operate properly or operates at a higher RPM than marked on the tool, the tool should be serviced to correct the cause before use.

Loctite® is a registered trademark of the Loctite Corp.

Optional: (to adjust throttle lever position)

Throttle lever is preset at the factory at an 11:00 o'clock position.

1. Secure valve body in vise using **52296** Repair Collar with motor housing pointing upwards.
2. Peel down rubber collar to expose **01461** Lock Nut.
3. Using a 34 mm crows foot and firmly holding motor housing, turn lock nut counter clockwise to loosen assembly.
4. Reposition throttle lever in desired position. Allow for additional torquing.
5. Using a 34 mm crows foot and torque wrench, tighten lock nut (torque 45 N•m/400 in. - lbs.).

Optional Accessories



Dynaswivel®

Swivels 360° at two locations which allows an air hose to drop straight to the floor, no matter how the tool is held.

- **94300** 1/4" NPT.



96049 Motor Tune-Up Kit

- Includes assorted parts to help maintain and repair motor.




Dynabrade Air Lube

- Formulated for pneumatic equipment.
- Absorbs up to 10% of its weight in water.
- Prevents rust and formation of sludge.
- Keeps pneumatic tools operating longer with greater power and less down time.

95842: 1pt. (473 ml)

95843: 1gal. (3.8 L)



52296 Repair Collar

- Specially designed collar for use in vise to prevent damage to valve body of tool during disassembly/assembly.