


# 4 hp, Type 1 Horizontal Grinder

## 6" & 8" Diameter, Governor Controlled

**Safety, Operation and Maintenance – Save This Document and Educate All Personnel**

Model	hp	Wheel Dia.	RPM	Exhaust
<b>53308</b>	4	6"	6,000	Side
<b>53312</b>	4	8"	4,500	Side

**GRINDER**



Find The Most Current Offering of Support Documents and Accessories at [www.Dynabrade.com](http://www.Dynabrade.com)

### **! WARNING**

Read and understand this tool manual before operating your air tool. Follow all safety rules for the protection of operating personnel as well as adjacent areas. Always operate, inspect and maintain this tool in accordance with the American National Standards Institute (ANSI), Safety Requirements for the Use, Care and Protection of Abrasive Wheels – ANSI B7.1, Compressed Air and Gas Institute (CAGI) Safety Code for Portable Air Tools – B186.1, Code of Federal Regulation – CFR 29 Part 1910, International Organization for Standardization (ISO) Hand Held Non-Electric Power Tools – ISO 11148, Safety Requirements and applicable State and Local Regulations.



Read and understand tool manual before work starts to reduce risk of injury to operator, visitors, and tool.



Eye protection must be worn at all times, eye protection to conform to ANSI Z87.1.



Ear protection to be worn when exposure to sound, exceeds the limits of applicable Federal, State or local statutes, ordinances and/or regulations.



Practice safety requirements. Work alert, have proper attire, and do not operate tools under the influence of alcohol or drugs.



Respiratory protection to be used when exposed to contaminants that exceed the applicable threshold limit values required by law.



Air line hazard, pressurized supply lines and flexible hoses can cause serious injury. Do not use damaged, frayed or deteriorated air hoses and fittings.

Some dust created by sanding, grinding, drilling, and other construction activities contain chemicals known to cause cancer, birth defects or other reproductive harm. Some examples of these chemicals are:

- Lead from lead-based paints
- Crystalline silica from bricks and cement and other masonry products
- Arsenic and chromium from chemically treated lumber

Your risk from these exposures varies, depending on how often you do this type of work. To reduce your exposure to these chemicals: work in a well ventilated area, and work with approved safety equipment, such as those dust masks that are specially designed to filter out microscopic particles.

### **SAFETY and OPERATING INSTRUCTIONS**



Carefully Read and Understand the General and Grinder sections found in Tool Safety and Operating Guidelines (PN00001676) Before Handling or Using Tool.

Carefully Read all instructions before operating or servicing any Dynabrade® Abrasive Power Tool. Products offered by Dynabrade are not to be modified, converted or otherwise altered from the original design.

**Tool Intent:** Industrial Horizontal Grinders are used to grind; metal, composites or stone surfaces using 6" or 8" Diameter, 1" wide with 5/8" center hole Type 1 reinforced grinding wheels.

**DO NOT USE Tool for Anything Other Than Its Intended Applications.**

**Training:** Proper care, maintenance, and storage of your air tool will maximize tools performance and reduce chance for accident.

**Employer's Responsibility:** Provide operators with safety instructions and training for safe use of tools and accessories.

**Report to Your Supervisor any Condition of the Tool, Accessories or Operation you Consider Unsafe.**

## MAINTENANCE INSTRUCTIONS

**Important:** To keep tool safe, a Preventative Maintenance Program is recommended. The program should include inspection of the tool and all related accessories and consumables, including air lines, pressure regulators, filters, oilers, etc. refer to CAGI B186.1 for additional maintenance information. If accessory or tool breakage occurs, investigate failure to determine the cause and correct before issuing tool for work. Use the following schedule as a starting point in developing a Preventative Maintenance Program. If tool does not operate properly (RPM, Vibration, Start/Stop) after these scheduled checks or at any time, the tool must be repaired and corrected before returning tool to use.

### INSTALLATION

- To ensure long life and dependable service, use a Closed Loop Air System and Filter-Regulator-Lubricator as diagramed below.
- Each tool should have its own dedicated hose connected to an air supply manifold. Quick disconnects should be installed at the manifold in an effort to reduce contamination into the tool.
- It is strongly recommended that all Dynabrade rotary vane air tools be used with a Filter-Regulator-Lubricator to minimize the possibility of misuse due to unclean air, wet air or insufficient lubrication. Dynabrade recommends the following: **10681** Air Line Filter-Regulator-Lubricator — Provides accurate air pressure regulation, two-stage filtration of water contaminants and micro-mist lubrication of pneumatic components.
- Dynabrade recommends one drop of air lube per minute for each 20 SCFM (example: if the tool specification states 40 SCFM, set the drip rate on the filter-lubricator to 2 drops per minute) Dynabrade Air Lube (P/N **95842**: 1pt/473ml) is recommended.

### MAINTENANCE SCHEDULE

#### Daily (every 8 hours):

- Inspect tool and accessories for damage or broken parts. Replace items as necessary to ensure proper operation and safety.
- Lubricate motor as recommended. Use Dynabrade Air Lube (P/N **95842**: 1pt/473ml) 10W/NR. (1 Drop per minute of air lube per 20 SCFM.)
- Check air line pressure with a gage. (MAX. 90 PSIG or 6.2 Bar operating pressure at the air inlet of the tool.)
- Right angled gear and wick system through gear case grease fitting with 3 plunges of gear oil (P/N **95848**) and grease gun (P/N **95541**). (Prime grease gun prior to greasing.)
- Check tool for proper operation: If operating improperly or demonstrates unusual vibration, the tool must be serviced and problem corrected before further use.

#### Every 20 Hours or Once a Week Which Ever Comes First:

- Check free speed of tool without the abrasive accessory mounted. Measure RPM (speed) with tachometer and with air pressure set at 90 PSIG while the tool is running. If a governed tool is operating at a higher speed than the RPM marked on the tool housing, the tool must be serviced and corrected before use. A non-governed tool may exceed the RPM marked on the tool by 10% when operated at free speed with no accessories.
- If tool is running fast look for worn, damaged or missing governors, air control rings and silencers. Special care must be taken when servicing

governors and speed control devices. Injection molded governor assemblies are non-serviceable and must be replaced.

- If tool is running slow look for clogged inlet screen, air stream, silencer(s) or a malfunctioning governor (see concerns for servicing governors). Service as required.

#### Every 50 Hours:

- Lubricate planetary gears through gear case grease fitting with 3 plunges of grease (P/N **95542**) and grease gun (P/N **95541**). (Prime grease gun prior to greasing.)

### REPAIR

- Use only genuine Dynabrade replacement parts to ensure quality. To order replacement parts, specify Model#, Serial# and RPM of your air tool.
- Mineral spirits are recommended when cleaning the tool and parts. Do not clean tool or parts with any solvents or oils containing acids, esters, ketones, chlorinated hydrocarbons or nitro carbons.
- DO NOT clean or maintain tools with chemicals that have a low flash point (example: WD-40®).
- Motor Tune-Up Kit are available (when applicable) which includes high wear and medium wear motor parts.
- Air tool markings must be kept legible at all times, if not, reorder housing and replace. User is responsible for maintaining specification information.
- After maintenance is performed on tool, add a few drops of Dynabrade Air Lube (P/N **95842**) to the tool inlet and start the tool a few times to lubricate air motor. Verify RPM (per 20 hr maintenance schedule), vibration and operation.

### HANDLING & STORAGE

- Use of tool rests, hangers and/or balancers is recommended.
- Protect tool inlet from debris (see Notice).
- DO NOT carry tool by air hose or near the tool throttle lever.
- Store accessories in protective racks or compartments to prevent damage.
- Follow the handling instructions outlined in the operating instructions when carrying the tool and when changing accessories.
- Protect accessories from exposure to water, solvents, high humidity, freezing temperature and extreme temperature changes.

### END OF USE/DISPOSAL


When tool has reached its end of useful service, disassemble tool into its primary components (i.e. steel, aluminum and plastic part) and recycle or discard per local, state and/or federal regulations as to not harm the environment.

### NOTICE


All Dynabrade motors use the highest quality parts and metals available and are machined to exacting tolerances. The failure of quality pneumatic motors can most often be traced to an unclean air supply or the lack of lubrication. Air pressure easily forces dirt or water contained in the air supply into motor bearings causing early failure. It often scores the cylinder walls and the rotor blades resulting in limited efficiency and power. Our warranty obligation is contingent upon proper use of our tools and cannot apply to equipment which has been subjected to misuse such as unclean air, wet air or a lack of lubrication during the use of this tool.

## AIR SYSTEM

Closed Loop Pipe System, Sloped in Direction of Air Flow



- Dynabrade Air Power Tools are designed to operate at 90 PSIG (6.2 Bar) maximum air pressure at the tool inlet, when the tool is running. Use recommended regulator to control air pressure.
- Ideally the air supply should be free from moisture. To facilitate removing moisture from air supply, the installation of a refrigerated air dryer after the compressor and the use of drain valves at each tool station is recommended.




**Models**

53308 - 6" Diameter

53312 - 8" Diameter

**Type 1 Horizontal Grinder  
Complete Assembly**



ITEM	P/N	DESCRIPTION	QTY.
1	55606 55608	(INCLUDES WARNING LABELS) 6" DIA. WHEEL GUARD 8" DIA. WHEEL GUARD	1
2	55624	RETAINING COLLAR & SCREW ASSY	1
3	95274	NUT	1
4	55666 55668	6" DIA. FRONT FLANGE 8" DIA. FRONT FLANGE	1
5	55665 55667	6" DIA. REAR FLANGE 8" DIA. REAR FLANGE	1
6	55641	COVER	1
7	98630	SEAL	1
8	98635	BEARING	2
9	95156	SCREW	4
10	95167	WASHER	4
11	55640	EXTENSION HANDLE	1
12	55652	SPINDLE	1
13	55661	KEY	1
14	01825	BEARING	1
15	98636	RETAINING RING	1
16	55646	FRONT BEARING PLATE	1
17	55644	CYLINDER	1
18	98641	PIN	2
19	55654	ROTOR	1
20	55658	VANE (4/PKG)	1
21	55648	REAR BEARING PLATE	1
22	55650	GASKET	1
23	98634	BEARING	1
24	95506	RETAINING RING	1
25	55683	GOVERNOR RETAINER	1
26	55616 55612	(INCLUDES GOVERNOR RETAINER) GOVERNOR ASSY. - 6" - 6,000 RPM GOVERNOR ASSY. - 8" - 4,500 RPM	1
27	55634 55632	(INCLUDES I.D. & WARNING LABELS) HOUSING ASSY. - 6" - 6,000 RPM HOUSING ASSY. - 8" - 4,500 RPM	1
28	98643	RIVET	8
29	95549	PIN	1
30	55670	THROTTLE LEVER	1
31	55671	SPRING	1
32	98637	SCREW	1
33	55672	LOCKOUT	1
34	95047	PIN	1
35	98638	SCREW	1
36	55673	SEAL	1
37	55680	SCREEN	1
38	98640	O-RING	1
39	95562	PLUG	1
40	55637	THROTTLE HANDLE ASSY. (INCLUDES 95562 PLUG)	1
41	95547	SCREW	2
42	98642	WASHER	2
43	18810	O-RING	1
44	55622	VALVE ASSEMBLY (INCLUDES 18810 O-RING)	1
45	55674	SPRING	1
46	03029	O-RING	1
47	55675	VALVE PLUG	1
48	55620	OIL REGULATOR	1
49	98639	O-RING	1
50	55678	SCREEN	1
51	55677	INLET BUSHING (1/2" NPT)	1
52	98508	OPEN END WRENCH - 2"	1
53	95135	HEX KEY WRENCH - 5/32"	1
54	55704	SUSPENSION BAIL	1

Model No., S/N,  
& RPM Plate  
Model 53308 - 96646  
Model 53312 - 96648

**ATTENTION**  
Fill Oil  
Reservoir  
Daily

**KEY**

- O** Oil: O<sub>1</sub> = Air Lube
- A** Adhesive: A<sub>2</sub> = Loctite #271  
A<sub>10</sub> = Loctite #243
- T<sub>x</sub>** X = Torque Value (N•m)
- T** Torque: N•m x 8.85 = lb•in.

Always follow adhesive manufacturers  
cleaning and priming recommendations.

**LIFETIME WARRANTY**

To validate Dynabrade Lifetime Warranty, you must register each tool at: [www.dynabrade.com](http://www.dynabrade.com). Registration of each tool at website is required. Dynabrade will not honor Lifetime Warranty on unregistered tools. Please view the entire Lifetime Warranty Policy at : [www.dynabrade.com](http://www.dynabrade.com).

**MACHINE SPECIFICATIONS**

Model	Speed	Power	Sound	Air Consumption	Wheel Size	Weight	Length
53308	6,000 RPM	4 hp (2,983 W)	90 db(A)	83 SCFM (2,350 LPM)	6" Dia.	15.7 lb. (7.1 kg)	22.4" (568 mm)
53312	4,500 RPM	4 hp (2,983 W)	87 db(A)	75 SCFM (2,123 LPM)	8" Dia.	17.2 lb. (7.8 kg)	22.8" (578 mm)

Additional Specifications: Air Inlet Thread 1/2" NPT • Hose I.D. 1/2" (15 mm)

Sound Level is the pressure measurement according to the method outlined in ISO regulation ISO-15744

**REQUIRED ACCESSORIES**

Whip hoses are required for safe operation of power tool.

Air line is to be between the tool and quick coupler.\*

\*All grinders with 4" diameter grinding wheels CAN NOT have a quick coupler fitting connected directly at the air inlet of tool. Tool must be directly connected to an air line. (ISO 11148)

**Flexible Air Line - Whip Hose**

- 1/2" I.D.
- Fittings: 1 Female and 1 Male

**Part No. 95870** 5' Length

**OPTIONAL ACCESSORIES****Motor Tune-Up Kit**

- Includes assorted parts to help maintain and repair motor.

**Part No. 96604**

**Dynabrade Air Lube**

- For pneumatic equipment.
- Absorbs up to 10% of its weight in water.
- Prevents rust and formation of sludge.

**Part No. 95821** 4 oz.

**Part No. 95842** 1 pt.

**REFERENCE CONTACT INFORMATION****American National Standards Institute (ANSI)**

1899 L Street, NW, 11th Floor • Washington, DC 20036  
Tel: 1 (202) 293-8020

**Compressed Air & Gas Institute (CAGI)**

1300 Sumner Ave. • Cleveland, OH 44115-2851  
Tel: 1 (216) 241-7333 • Fax: (216) 241-0105

**Government Printing Office (GPO)**

Superintendent of Documents • Attn: New Orders  
P.O. Box 371954 • Pittsburgh, PA 15250-7954 • Tel: 1 (202) 512-1803

**International Organization of Standards (ISO)**

Case postale 56 • CH-1211 Geneva 20  
Tel: + 41 22 749 01 11 • Fax: + 41 22 749 09 47

**DYNABRADE, INC.**

8989 Sheridan Drive • Clarence, NY 14031-1419 • Phone: 716-631-0100 • Fax: 716-631-2073 • International Fax: 716-631-2524  
©DYNABRADE, INC., 2013 PRINTED IN USA PD13.18\_06/13

[www.dynabrade.com](http://www.dynabrade.com)

